



## ZB200 Compact 200 S460J0 BS5400 HA+20HB Extra Wide Heavy Load Bailey Bridge

### Basic Information

- Place of Origin: China
- Brand Name: Tongkai
- Certification: ISO, EN1090, SGS, CIDB
- Model Number: ZB200
- Minimum Order Quantity: 1 set
- Price: 1000USD ~1800USD/ton
- Packaging Details: Nude and Steel case
- Delivery Time: 15~45days
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 3000/month



### Product Specification

- Material: S460J0, S355JR, S355J0, Gr65, Gr50
- Load: HA, HB, HA+20HB AASHTO HL-93, HS35-44
- Lane: Single Lane 3.15m~4.2m Double Lane 7.35m
- Surface Finish: Painted Or Galvanized
- Highlight: **BS5400 Bailey Bridge, Heavy Load Bailey Bridge, ZB200 Bailey Bridge**



### More Images



Our Product Introduction

for more products please visit us on [tkbridges.com](http://tkbridges.com)

## Product Description

### PRODUCT DESCRIPTION

ZB 200 Bridge is the 'hot product' of the TONGKAI modular steel bridge system. The ZB 200 Bridge is the ideal solution for rapid, durable and worthy for permanent or temporary bridging, humanitarian aid and disaster relief operation, replacement of damaged bridge, and provides the flexibility to bridge designers and contractors.

The ZB 200 Bridge uses standardized components, or super panel and a selection of decking systems to create a versatile heavy-duty modular steel bridge system with a clear spanning capability of up to 60.96 m (200 ft). The ZB 200 Bridge system combines strong and durable structure with high speed of construction to provide significant advantages over more traditional bridge construction techniques even in the limited access locations such as rural area or disaster stricken area.

### APPLICATION

Permanent or semi-permanent bridging  
Long term temporary bridging  
Rural infrastructure project  
Urban traffic project  
Humanitarian aid and disaster relief operation  
Pedestrian bridging  
Services pipelines  
Construction site access  
Replacement of damaged bridge  
Emergency response stock

### Technical Specification

Span	9.144m(30ft) upto 60.96m(200ft)
Road Width	single lane 3.15m/4.2m ; double lane 7.35m
Material Grade	S460J0,S355JR,GR65,GR50
Load Capacity	HL-93,HS25-44, HA ,HA+20HB
Surface Finish	Painted or Galvanized
Joint System	Pin and Bolt System
Erection Method	Crane lifting , Cantilever Launching Method



Zhenjiang Tongkai Mechanical Engineering Co.,Ltd.



008613813883197



[andy@tkmachinery.com](mailto:andy@tkmachinery.com)



[tkbridges.com](http://tkbridges.com)

Room 202, Jintai Building, Runxing Road, High tech Zone, Zhenjiang Jiangsu, China