



ZB200 S460J0 BS5400 HA+20HB Bailey Bridge

Our Product Introduction

Basic Information


- Place of Origin: China
- Brand Name: Tongkai
- Certification: ISO,EN1090,SGS ,CIDB
- Model Number: ZB200/TK200/Compact 200
- Minimum Order Quantity: 1 set
- Price: 1500USD ~2000USD/ton
- Packaging Details: Nude and Steel case
- Delivery Time: 15~45days
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 3000/month



for more products please visit us on tkbridges.com

Product Specification

- Material: S460J0,S355JR,S355J0,Gr65,Gr50
- Load: HA ,HB,HA+20HB AASHTO HL-93,HS35-44
- Lane: Single Lane 3.15m~4.2m Double Lane 7.35m, Three Lane 10.5m
- Surface Finish: Painted Or Galvanized
- Deck: Anti Skid Aggregate
- Highlight: ZB200 Bailey Bridge, S460J0 Bailey Bridge, BS5400 steel bailey bridge



More Images



Product Description

PRODUCT DESCRIPTION

ZB 200 Bridge is the 'hot product' of the TONGKAI modular steel bridge system. The ZB 200 Bridge is the ideal solution for rapid, durable and worthy for permanent or temporary bridging, humanitarian aid and disaster relief operation, replacement of damaged bridge, and provides the flexibility to bridge designers and contractors.

ZB 200 Bridge uses standardized components, or super panel and a selection of decking systems to create a versatile heavy-duty modular steel bridge system with a clear spanning capability of up to 60.96 m (200 ft). The ZB 200 Bridge system combines strong and durable structure with high speed of construction to provide significant advantages over more traditional bridge construction techniques even in the limited access locations such as rural area or disaster stricken area.

APPLICATION

- Permanent or semi-permanent bridging
- Long term temporary bridging
- Rural infrastructure project
- Urban traffic project
- Humanitarian aid and disaster relief operation
- Pedestrian bridging
- Services pipelines
- Construction site access
- Replacement of damaged bridge
- Emergency response stock

Features

- Modular
- Rapid-build
- Can be assembled using light plant
- Can be crane built or cantilever launched
- Relocatable
- Transport in standard containers
- Long span capability
- Single and multi-span solutions available
- Robust
- High fatigue capability
- Heavy axle / Wheel load capacity
- Long life with minimal maintenance
- Optional ramps, footwalks, piers, parapets and barriers
- Various deck options available

Technical Specification

Span	9.144m upto 60.96m
Road Width	single lane 3.15m/4.2m ; double lane 7.35m
Material Grade	S460J0,S355JR,GR65,GR50
Load Capacity	HL-93,HS25-44, HA ,HA+20HB
Surface Finish	Painted or Galvanized
Joint System	Pin and Bolt System
Erection Method	Crane lifting , Cantilever Launching Method



Zhenjiang Tongkai Mechanical Engineering Co.,Ltd.



008613813883197



andy@tkmachinery.com



tkbridges.com

